

真诚打造信誉 · 追求更高品位
Create Sincere Credit, Go In For Higher Level



FUELING EQUIPMENT

Afford Reassurance Products, Keep Excellent Service

AILE® 上海爱乐加油设备制造有限公司 SHANGHAI AILE FUELING EQUIPMENT MFG. CO., LTD.

公司地址: 上海市嘉定区澄浏中路888号 Add: 888 Chengliu Mid. Rd. Madong Industrial Zone
电 话: +86-21-59900396 Malu Town Jiading Shanghai China.
+86-21-59900195 Tel: +86-21-59900396 +86-21-59900195
传 真: +86-21-59900397 Fax: +86-21-59900397

中国 · 上海
CHINA · SHANGHAI

不懈追求, 不断创新...



AILE®
www.aile-fc.com

品 / 质 / 源 / 于 / 真 / 诚

AILE® 上海爱乐加油设备制造有限公司 SHANGHAI AILE FUELING EQUIPMENT MFG. CO., LTD.

公司简介 Company Profile



上海爱乐加油设备制造有限公司成立于2005年, 是一家集加油站设备以及信息系统的研发、生产、销售于一体的民营高科技企业。同时是安徽省唯一自主生产税控燃油加油机的企业, 得到了国家税务总局、北京计量技术研究院及省质量技术监督局的大力支持。

爱乐公司不仅拥有先进的技术设备及高科技的人才, 而且可提供加油站整体配置方案及系统集成和工程施工服务。

公司厂房面积2000多平方米, 办公楼600平方米, 总投资1千万人民币, 引进全套数控钣金及加工设备, 年加油机生产能力可达到5000多台。

在技术方面, 公司自行研制开发的中升系列加油机, 目前产品已远销国内外, 质量获得一致好评。

在产品品质方面, 其产品符合税控燃油加油机JJG443-2006国家标准。公司通过ISO9001国际质量体系认证、国家防爆电气产品质量监督检验中心认证。

立足现在, 展望未来! 本公司愿为国家燃油附加税政策的实施, 做出应有的贡献。



企业资质 ENTERPRISE QUALIFICATION

ENTERPRISE QUALIFICATION





新款经济型加油机

Aile Series
ZS09111J(Y)
ZS09222J(Y)

黄山系列

统制00000145号
Aile Manufacturing NO.00000145

单油品单枪 双油品双枪

外观尺寸: 2100×880×500(mm)



技术参数

流量范围: (5~55) L/min 最大允许误差: $\pm 0.3\%$ 最小被测量: 5L
噪音: ≤ 80 dB(A) 进口真空度: ≥ 54 kPa 单次计数范围: 体积/金额: 0~9999.99L/yuan
电源: AC220V 50Hz AC380V 50Hz 累计计数范围: 体积/金额: 0~999999.99L/yuan
额定功率: 750W 环境温度: $-40^{\circ}\text{C} \sim +55^{\circ}\text{C}$ 单价范围: 0~99.99元/L 相对湿度: 30%~90%
Range of flow: (5~55) L/min Max. tolerance: $\pm 0.3\%$ Min. measured volume: 5L
Noise: ≤ 80 dB(A) Inlet vacuity: ≥ 54 kPa Scope of unit price: 0~99.99yuan/L
Range of single counting Volume/ Amount: 0~9999.99L/yuan
Range of accumulative counting Volume/ Amount: 0~999999.99L/yuan
Power supply: AC220V 50Hz AC380V 50Hz Rated power: 750W
Ambient temp: $-40^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Relative humidity: 30%~90%

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the practical product, if there is any change about the specification, color, configuration, color of our product.

黄山系列




产品特点

- 流线型外观设计, 简洁、大方。
- 高精度流量计使用计量更准确、寿命更长。
- 大屏幕液晶显示 (采用感光灯开关) 及不锈钢的使用。
- 工业级电脑设计, 运行更稳定可靠, 操作简单方便。
- 可选IC卡联动功能, 可直接与后台计算机联网。
- 优良的电磁兼容和抗干扰性能。
- 防雨、防潮、防沙、防爆性能良好。



外观尺寸: 2100×880×500



底座安装图

- Succinct, tasteful, streamline-designed outward appearance.
- Highly-accurate flowmeter making the measurement more accurate and service life longer.
- Big-screen liquid crystal display (using photosensitivity light switch) and the use of stainless steel.
- Computers with industry-level design, making the movement more stable and reliable, easy and convenient to operate.
- Having linkage function with IC card machines and directly making network with the backstage computer.
- Having fine electromagnetic compatibility and interference-resistant property.
- Having fine rain-proof, moisture-proof, sandproof and explosion-proof properties.

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the practical product, if there is any change about the specification, color, configuration, color of our product.



统制00000145号
Aile Manufacturing NO.00000145

鼎峰系列

鼎峰系列



FUELING EQUIPMENT

鼎峰系列新型加油机



鼎峰系列 单油品单枪 ZS06111J

尺寸: 2160×960×460(mm)

产品特点:

- ★ 流线型外观设计, 简洁大方。
- ★ 高精度流量计使用计量更准确、寿命更长。
- ★ 大屏幕液晶显示及背光电源的使用。
- ★ 工业电脑控制, 运行稳定可靠, 操作简单方便。
- ★ 可选IC卡联动功能, 可直接与后台计算机联网。
- ★ 优良的电磁兼容和抗干扰性能。
- ★ 防雨、防潮、防沙、防爆性能较高。

ZS-06111J(Y)


- Succinct, tasteful, streamline-designed outward appearance.
- Highly-accurate flowmeter making the measurement more accurate and service life longer.
- Big-screen liquid crystal display (using photosensitivity light switch) and the use of stainless steel.
- Computers with industry-level design, making the movement more stable and reliable, easy and convenient to operate.
- Having linkage function with IC card machines and directly making network with the backstage computer.
- Having fine electromagnetic compatibility and interference-resistant property.
- Having fine rain-proof, moisture-proof, sandproof and explosion-proof properties.

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the practical product, if there is any change about the specification, color, configuration, color of our product.


技术参数

流量范围: (5~55) L/min 最大允许误差: $\pm 0.3\%$ 最小被测量: 5L
噪音: ≤ 80 dB(A) 进口真空度: ≥ 54 kPa 单次计数范围: 体积/金额: 0~9999.99L/yuan
电源: AC220V 50Hz AC380V 50Hz 累计计数范围: 体积/金额: 0~999999.99L/yuan
额定功率: 750W 环境温度: $-40^{\circ}\text{C} \sim +55^{\circ}\text{C}$ 单价范围: 0~99.99元/L 相对湿度: 30%~90%

Range of flow: (5~55) L/min Max. tolerance: $\pm 0.3\%$ Min. measured volume: 5L
Noise: ≤ 80 dB(A) Inlet vacuity: ≥ 54 kPa Scope of unit price: 0~99.99yuan/L
Range of single counting Volume/ Amount: 0~9999.99L/yuan
Range of accumulative counting Volume/ Amount: 0~999999.99L/yuan
Power supply: AC220V 50Hz AC380V 50Hz Rated power: 750W
Ambient temp: $-40^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Relative humidity: 30%~90%



外观尺寸: 2160×960×460



底座安装图

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the practical product, if there is any change about the specification, color, configuration, color of our product.

产品展示
Product Display

鼎峰系列

鼎峰系列

AILE®
www.aile.com

MC 院制00000145号
Aile manufacturing NO. 00000145

双油品单枪
ZS06111J(Y)
ZS06222J(Y)
尺寸: 2160×960×460 (mm)



ZS-06111J(Y)

产品特点:

- 流线型外观设计, 简洁大方。
- 高精度流量计使用计量更准确, 寿命更长。
- 大屏幕液晶显示及背光电源的使用。
- 工业电脑控制, 运行稳定可靠, 操作简单方便。
- 可选IC卡机联动功能, 可直接与后台计算机联网。
- 优良的电磁兼容和抗干扰性能。
- 防雨、防雾、防沙、防爆性能较高。

ZS-06111J(Y)


- Succinct, tasteful, streamline-designed outward appearance.
- Highly-accurate flowmeter making the measurement more accurate and service life longer.
- Big-screen liquid crystal display (using photoconductivity light switch) and the use of stainless steel.
- Computers with industry-level design, making the movement more stable and reliable, easy and convenient to operate.
- Having linkage function with IC card machines and directly making network with the backstage computer.
- Having fine electromagnetic compatibility and interference-resistant property.
- Having fine rain-proof, measure-proof, sandproof and explosion-proof properties.

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture. If there is any change about the specification, model, configuration, color of our product.


ZS06111J(Y)

技术参数

流量范围: (5~55) L/min 最大允许误差: ±0.3% 最小被测量: 5L
噪音: ≤80dB(A) 进口真空度: ≥54kPa 单次计数范围: 体积/金额: 0~9999.99L/yuan
电源: AC220V 50Hz AC380V 50Hz 累计计数范围: 体积/金额: 0~999999.99L/yuan
额定功率: 750W 环境温度: -40℃~+55℃ 单价范围: 0~99.99元/L 相对湿度: 30%~90%



外观尺寸: 2160×960×460



ZS06222J(Y)

Range of flow: (5~55)L/min Max. tolerance: ±0.3% Min. measured volume: 5L
Noise: ≤80dB(A) Inlet vacuity: ≥54kPa Scope of unit price: 0~99.99yuan/L
Range of single counting Volume/ Amount: 0~9999.99L/yuan
Range of accumulative counting Volume/ Amount: 0~999999.99L/yuan
Power supply: AC220V 50Hz AC380V 50Hz Rated power: 750W
Ambient temp: -40℃~+55℃ Relative humidity: 30%~90%

单油品单枪
ZS06111J(Y)

尺寸: 2160×960×460 (mm)

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture. If there is any change about the specification, model, configuration, color of our product.

5

6

产品展示
Product Display

中星系列

中星系列

AILE®
www.aile.com

MC 院制00000145号
Aile manufacturing NO. 00000145

(可选配潜油泵机)
ZS08222J(Y) ZS08424J(Y)
2360×1050×520 (mm)

(可选配潜油泵机)
ZS08222J(Y) ZS08424J(Y)
2360×1050×520 (mm)




产品特点


- 流线型外观设计, 简洁, 大方。
- 高精度流量计使用计量更准确, 寿命更长。
- 大屏幕液晶显示(采用感光灯开关)及不锈钢的使用。
- 工业电脑设计, 运行更稳定可靠, 操作简单方便。
- 可选IC卡机联动功能, 可直接与后台计算机联网。
- 优良的电磁兼容和抗干扰性能。
- 防雨、防雾、防沙、防爆性能较好。

- Succinct, tasteful, streamline-designed outward appearance.
- Highly-accurate flowmeter making the measurement more accurate and service life longer.
- Big-screen liquid crystal display (using photoconductivity light switch) and the use of stainless steel.
- Computers with industry-level design, making the movement more stable and reliable, easy and convenient to operate.
- Having linkage function with IC card machines and directly making network with the backstage computer.
- Having fine electromagnetic compatibility and interference-resistant property.
- Having fine rain-proof, measure-proof, sandproof and explosion-proof properties.

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture. If there is any change about the specification, model, configuration, color of our product.



外观尺寸: 2360×1050×520



技术参数

流量范围: (5~55) L/min 最大允许误差: ±0.3% 最小被测量: 5L
噪音: ≤80dB(A) 进口真空度: ≥54kPa 单次计数范围: 体积/金额: 0~9999.99L/yuan
电源: AC220V 50Hz AC380V 50Hz 累计计数范围: 体积/金额: 0~999999.99L/yuan
额定功率: 750W 环境温度: -40℃~+55℃ 单价范围: 0~99.99元/L 相对湿度: 30%~90%

Range of flow: (5~55)L/min Max. tolerance: ±0.3% Min. measured volume: 5L
Noise: ≤80dB(A) Inlet vacuity: ≥54kPa Scope of unit price: 0~99.99yuan/L
Range of single counting Volume/ Amount: 0~9999.99L/yuan
Range of accumulative counting Volume/ Amount: 0~999999.99L/yuan
Power supply: AC220V 50Hz AC380V 50Hz Rated power: 750W
Ambient temp: -40℃~+55℃ Relative humidity: 30%~90%

7

8

产品展示

中华系列

院制00000145号
AILE manufacturing NO. 00000145

ZS06222 ZS06111
1600×860×480mm
(外贸机型)

AILE

中华系列

大流量加油机

外观尺寸: 1600×860×480 (mm)

产品特点

- 流线型外观设计, 简洁, 大方。
- 高精度流量计使计量更准确, 寿命更长。
- 大屏幕液晶显示(采用感光灯开关)及不锈钢的使用。
- 工业级电脑设计, 运行更稳定可靠, 操作简单方便。
- 可选IC卡联动功能, 可直接与后台计算机联网。
- 优良的电磁兼容和抗干扰性能。
- 防雨、防潮、防沙、防爆性能良好。





- Succinct, tasteful, streamline-designed outward appearance.
- Highly-accurate flowmeter making the measurement more accurate and service life longer.
- Big-screen liquid crystal display (using photosensitivity light switch) and the use of stainless steel.
- Computers with industry-level design, making the movement more stable and reliable, easy and convenient to operate.
- Having linkage function with IC card machines and directly making network with the backstage computer.
- Having fine electromagnetic compatibility and interference-resistant property.
- Having fine rain-proof, moisture-proof, sandproof and explosion-proof properties.

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture, if there is any change about the specification, model, configuration, color of our product.

技术参数

流量范围: (5~55) L/min 最大允许误差: ±0.3% 最小被测量: 5L
噪音: ≤80dB(A) 进口真空度: ≥54kPa 单次计数范围: 体积/金额: 0~9999.99L/yuan
电源: AC220V 50Hz AC380V 50Hz 累计计数范围: 体积/金额: 0~999999.99L/yuan
额定功率: 750W 环境温度: -40℃~+55℃ 单价范围: 0~99.99元/L 相对湿度: 30%~90%
Range of flow: (5~55) L/min Max. tolerance: ±0.3% Min. measured volume: 5L
Noise: ≤80dB(A) Inlet vacuity: ≥54kPa Scope of unit price: 0~99.99yuan/L
Range of single counting: Volume/Amount: 0~9999.99L/yuan
Range of accumulative counting: Volume/Amount: 0~999999.99L/yuan
Power supply: AC220V 50Hz AC380V 50Hz Rated power: 750W
Ambient temp: -40℃~+55℃ Relative humidity: 30%~90%



外观尺寸: 1600×860×480

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture, if there is any change about the specification, model, configuration, color of our product.

9

10

产品展示

车载系列

单油品单枪
中升ZS07111
560×480×380mm



12V/24V车载加油机
MOBILE DISPENSER WITH 12V/24V PUMP



大流量车载机
MOBILE FUEL DISPENSER WITH BIG FLOW



常规车载机
MOBILE DISPENSER FOR OIL TRUCK

产品特点

车载系列加油机是利用车带油泵为动力进行流动性加油, 可满足流动售油的需求, 具有普通税控加油机的各项功能。适用于汽油、柴油、乙醇等轻质燃料。中升车载加油机具有体积小, 功能齐全, 外观美观等特点。

FEATURES:

This kind of truck carrier fuel dispenser is make use of the power from the pump of the truck to fueling, which can meet the need of movable fuel dispensing. This dispensing has the same function as other kind of dispensers. It has a small body with complete function and stainless steel cover, can be used in gasoline, diesel oil, ethanol fuel and so on.

流量范围: (5~55/75) L/min	最大允许误差: ±0.3% 最小被测量: 5L
噪音: 无噪音 进口真空度: ≥54kPa	单次计数范围: 体积/金额: 0~9999.99升/元
电源: DC12V DC24V	累计计数范围: 体积/金额: 0~999999.99升/元
环境温度: -40℃~+55℃	单价范围: 0~99.99元/升 相对湿度: 30%~90%

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture, if there is any change about the specification, model, configuration, color of our product.

车载系列

单油品单枪
中升ZS07111J
800×550×390/460mm



产品特点

- ☆ 流线型外观设计, 简洁、大方;
- ☆ 大流量供油 85L/min;
- ☆ 高精度流量计使计量更准确、寿命更长;
- ☆ 大屏幕液晶显示, 背光电源的使用;
- ☆ 工业级电脑设计, 运行更稳定可靠, 操作简单方便;
- ☆ 优良的电磁兼容和抗干扰性能;
- ☆ 可选IC卡联动功能, 可直接与后台计算机联网;
- ☆ 防雨、防潮、防沙、防爆性能良好;
- ☆ 适用于油罐车、轮船及单位内部供油等。

FEATURES:

- ☆ Succinct, tasteful, streamline-designed outward appearance.
- ☆ The flow of oil 85L/min.
- ☆ Highly-accurate flowmeter making the measurement more accurate and service life longer.
- ☆ Big-screen liquid crystal display, the backlight power of using.
- ☆ Computers with industry-level design, making the movement more stable and reliable, easy and convenient to operate.
- ☆ Having fine electromagnetic compatibility and interference resistant property.
- ☆ Having linkage function with IC card machines and directly making network with the backstage computer.
- ☆ Having fine rain-proof, moisture, sandproof and explosion-proof properties.
- ☆ It can be used in the tank truck, ship and company intestine.

流量范围: (5~55) L/min	最大允许误差: ±0.3% 最小被测量: 5L
噪音: ≤80dB(A) 进口真空度: ≥54kPa	单次计数范围: 体积/金额: 0~9999.99升/元
电源: AC 220V 50Hz AC380V 50Hz	累计计数范围: 体积/金额: 0~999999.99升/元
额定功率: 750W 环境温度: -40℃~+55℃	单价范围: 0~99.99元/升 相对湿度: 30%~90%

产品规格、型号、配置、颜色如有更改, 请以产品实物为准
Please refer to the product picture, if there is any change about the specification, model, configuration, color of our product.

11

12

产品展示
Product Display

加油站管理系统

STATION MANAGE SYSTEM



产品规格、型号、重量、结构如有更改，请以产品实物为准
Product type, to the product manual, if there is any change about the specification, model, weight, structure, please refer to the product.

13

AILE®
www.aile-td.com

加油机智能IC卡

IC CARD SYSTEM

IC卡智能加油机内置了IC卡加油终端，并配备了功能完备的IC卡操作软件，语音系统，其主要功能有：

卡机联动

可以识别和确定IC卡，从而彻底杜绝非有效卡实施操作的可能，用户可以通过智能管理卡自行选择加油机的各种不同的工作方式。

兼容多种卡型

普通的逻辑加密卡或功能更强的CPU卡都可以使用，而且通过更换软件，还可以兼容已有的加油卡和银行卡。

支持操作三类卡

智能管理卡、油卡和现金卡，智能管理卡可以设定加油机联网模式，设定加油机工作模式，还可以修改加油机参数；油卡及储值卡，必须按照指定的油品实施加油，加油量按实际加油体积从卡中自动扣除；现金卡可以选择任何一种油品加油，加油量按实际加油的应付金额从卡中自动扣除。

黑名单管理

可以对IC卡进行挂失，或对折叠，报废的IC卡重新补卡，有效地保证了IC卡的使用安全。

联网操作

通过中心结算系统达到多个加油站联网操作，把IC卡的使用范围最大化。



Intelligent IC Card

With the IC card terminal and software, the NEW Century dispenser

is able to perform the following functions:

Operate the Dispenser with IC Card

The system is able to identify the IC card to prevent unauthorized use of the machine.

The manager is able to set the operation mode of the dispenser.

Compatible Diverse IC Cards

Such as logical security card, powerful CPU card, etc.

Card of Different Type Applicable to the Zhong Sheng Dispenser Series

With the intelligent card, the manager is able to set the way in which the dispenser works and change the parameter of the machine. With the deposit card for assigned product, the machine will dispense the assigned product only.

the volume will be deducted from the card. The customer may choose any product to be dispensed with the cash card and cash amount will be deducted from the card accordingly.

Black List Management

The manager is able to issue a new card for the destroyed or defective card and accept report for lost, which makes the IC card safe to use.

Connecting with GSK0000 Station Manage System

With the central accounting system, the IC card work in different gas stations.



潜油泵电控柜
SUBMERSIBLE PUMP ELECTRIC BOX

14